



# Axalta™ Silicone Remover 200 Slow



---

## GENERAL

### DESCRIPTION

A slow evaporating solvent mixture used primarily to remove oil and grease residues.

This product is used for cleaning sanded, old or original finishes, and surfaces coated with primer or surfacer which have been subsequently sanded.

**The products referenced herein may not be available for sale in your market. Please consult your distributor for product availability.**



---

## MIXING

### COMPONENTS

Axalta™ Silicone Remover 200 Slow

### MIX RATIO

Ready-to-Use

### SPECIAL TIPS

1. Always use a clean cloth when wiping away Axalta Silicone Remover 200 Slow.
2. Do not allow Axalta Silicone Remover 200 Slow to dry on the surface.
3. Allow cleaned surfaces to dry completely before recoating.
4. Heavily soiled areas need to be cleaned more than once.
5. This product is not suitable for cleaning spray guns or tools or removing release agents from raw plastic parts.
6. Axalta Silicone Remover 210 Water or Axalta Silicone Remover 220 Low VOC must be used for final cleaning prior to use of any waterborne products.



---

## APPLICATION

### FIELD OF APPLICATION

For cleaning surfaces prior to applying primers, surfacers, or top coats.

### PROCEDURE

- Apply Axalta Silicone Remover 200 Slow with a spray bottle or clean cloth.
- Wipe dry with a clean cloth before Axalta Silicone Remover 200 Slow evaporates.



---

## DRY TIMES

### AIR DRYING

Slow evaporating.



## PHYSICAL PROPERTIES

**Coating Category:** Surface Preparation  
 Max. VOC (AP/LE): 776 g/l; 6.5 lbs/gal  
 Avg. Gallon Weight: 776 g/l; 6.5 lbs/gal  
 Avg. Weight % Volatiles: 100%  
 Avg. Weight % Water: 0.0%  
 Avg. Weight % Exempt Solvent: 0.0%  
 Avg. Volume % Water: 0.0%  
 Avg. Volume % Exempt Solvent: 0.0%

## VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies, and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

**Revised: September 2019**

**In the United States:**  
**1.855.6.AXALTA**  
**axalta.us**

**In Canada:**  
**1.800.668.6945**  
**axalta.ca**

