



# 790™ Quick N' Easy Clear Blender



## GENERAL

### DESCRIPTION

An easy to use blender developed to improve the appearance of clearcoat blends. It is conveniently packaged in an aerosol can for minimum waste generation and cleanup.

The products referenced herein may not be available for sale in your market. Please consult your distributor for product availability.



## MIXING

### MIX RATIO

Ready-to-spray

### POT LIFE

Indefinite



## APPLICATION

### SUBSTRATES

Properly prepared and cleaned OEM finishes.

### SURFACE PREPARATION

Step 1: Sand repair area with a DA disc P500-P600

Step 2: Sand surrounding area with P1000-P1500 for the basecoat blend

Step 3: Sand the clearcoat blend area with P3000

### APPLICATION

Panel repair is the approved procedure for warranty repair. If the refinisher chooses to blend, follow the steps below. The following steps assume appropriate preparation of the blend area has been performed per the steps in the Surface Preparation section above, and that the basecoat blend has been completed.

Step 1: Apply your first coat of clearcoat slightly beyond the base coat blend, immediately apply 1 light coat of 790™ Quick N' Easy Clear Blender to the clearcoat overspray edge

Step 2: Apply the second coat of clearcoat, staying just inside the P3000 grit prepared area immediately apply 1 or more light coat(s) of 790™ Quick N' Easy Clear Blender to the clearcoat overspray edge, until a smooth transition has been achieved.



## DRY TIMES

Allow to dry according to clearcoat product recommendations



## PHYSICAL PROPERTIES

PWMIR Category:	Clear Coating Products (CCP)
MIR:	1.4
Max. VOC (AP):	762 g/L (6.4 lbs./gal)
Avg. Gallon Weight:	791 g/L (6.60 lbs./gal)
Avg. Weight % Volatiles:	96.3%
Avg. Weight % Water:	0.0%
Avg. Weight % Exempt Solvent:	0.0%
Avg. Volume % Water:	0.0%
Avg. Volume % Exempt Solvent:	0.0%
Flash Point:	See MSDS/SDS

## VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: February 2015

In the United States:  
**1.855.6.AXALTA**  
**axalta.us**

In Canada:  
**1.800.668.6945**  
**axalta.ca**

