

# SAFETY DATA SHEET

7985S v3.0  
en/US



## 1. Identification of the substance/mixture and of the company/undertaking

<b>Product name</b>	Activator-Reducer Medium	
<b>Product code</b>	7985S	Formula Date: 2008-04-15
<b>Intended use</b>	Hardener for professional use	
	Axalta Coating Systems, LLC Applied Corporate Center 50 Applied Bank Boulevard, Suite 300 US Glen Mills, PA 19342	
<b>Telephone</b>	Product information	(855) 6-AXALTA
	Medical emergency	(855) 274-5698
	Transportation emergency	(800) 424-9300 (CHEMTREC)

## 2. Hazards identification

This preparation is hazardous per the following GHS criteria

### GHS-Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitisation	Category 1
Target Organ Systemic Toxicant - Single exposure	Category 3
Target Organ Systemic Toxicant - Repeated exposure	Category 2

Endpoints which are "not classified", "cannot classified" and "not applicable" are not shown.

### GHS-Labeling



Hazard symbols

Signal word

Warning

Hazard statements

Flammable liquid and vapour.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.  
May cause an allergic skin reaction.  
Causes skin irritation.  
Causes serious eye irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Use only outdoors or in a well-ventilated area.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Contaminated work clothing should not be allowed out of the workplace.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.

## SAFETY DATA SHEET

7985S v3.0  
en/US



IF ON SKIN: Wash with plenty of soap and water.  
Specific treatment (see supplemental first aid instructions on this label).  
If skin irritation or rash occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Dispose of contents/container in accordance with local regulations.

### Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

## 3. Composition/information on ingredients

Mixture of synthetic resins and solvents

### Components

CAS-No.	Chemical Name	Concentration
28182-81-2	Aliphatic polyisocyanate resin	48 - 59%
123-86-4	Butyl acetate	15 - 26%
1330-20-7	Xylene	10%
110-43-0	Methyl amyl ketone	4 - 15%
100-41-4	Ethylbenzene	2.6%
763-69-9	Ethyl 3-ethoxy propionate	1 - 4%

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Non-regulated ingredients 0.1 - 1.0%  
OSHA Hazardous: Yes

## 4. First aid measures

### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

### Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

### Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

## SAFETY DATA SHEET

7985S v3.0  
en/US



### Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

### Most Important Symptoms/effects, acute and delayed

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. Skin contact may cause skin sensitization.

#### Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

#### Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

#### Extinguishing media which shall not be used for safety reasons

High volume water jet

#### Hazardous combustion products

CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

#### Fire and Explosion Hazards

Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

#### Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## 6. Accidental release measures

#### Procedures for cleaning up spills or leaks

Ventilate area. Remove sources of ignition. Do not breathe vapors. Do not get in eyes or on skin. Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TM 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance) Confine and remove with inert absorbent. Pressure can be generated. Do not seal waste containers for 48 hours to allow CO<sub>2</sub> to vent. After 48 hours, material may be sealed and disposed of properly.

#### Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

## SAFETY DATA SHEET

7985S v3.0  
en/US



## 7. Handling and storage

### Precautions for safe handling

Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY CAUSE FLASH FIRE. Close container after each use. Ground containers when pouring. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F). If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

### Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

### Storage

#### Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Advice on common storage

Store separately from oxidizing agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Precautions should be taken to avoid exposure to atmospheric humidity or water. Evolution of CO<sub>2</sub> in closed containers causes overpressure and produces a risk of bursting.

#### Additional information on storage conditions

Precautions should be taken to avoid exposure to atmospheric humidity or water. Humid air and/or water will produce carbon dioxide which will pressurize the container. Open drum carefully as content may be under pressure.

OSHA/NFPA Storage Classification: IC

## 8. Exposure controls/personal protection

### Engineering controls and work practices

Provide adequate ventilation. Air-fed protective respiratory equipment must be worn by spray operator even when good ventilation is provided.

### National occupational exposure limits

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
123-86-4	Butyl acetate	ACGIH	15 min	STEL	200 ppm	
			8 hr	TWA	150 ppm	
		OSHA	8 hr	TWA	150 ppm	
1330-20-7	Xylene	ACGIH	15 min	STEL	150 ppm	
			8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	100 ppm	

## SAFETY DATA SHEET

7985S v3.0  
en/US



CAS-No.	Chemical Name	Source	Time	Type	Value	Note
110-43-0	Methyl amyl ketone	ACGIH	8 hr	TWA	50 ppm	
		OSHA	8 hr	TWA	100 ppm	
100-41-4	Ethylbenzene	ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	25 ppm	

\*\* STEL = Short term exposure limit.  
TWA = Time-weighted average.

### Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

### Respiratory protection

Do not breathe vapors or mists. Wear a positive-pressure, supplied air respirator (NIOSH approved TC-19C), while mixing activator with paint, during application and until all vapors and spray mists are exhausted. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Refer to the hardener/activator label instructions for further information. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed to vapor or spray mist.

### Eye protection

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

### Skin and body protection

Neoprene gloves and coveralls are recommended.

### Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

### Environmental exposure controls

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

## 9. Physical and chemical properties

### Appearance

Form: liquid    Colour: clear    Odour: Characteristic Paint Odor

Flash point	95 °F
Lower Explosive Limit	1 %
Upper Explosive Limit	7.9 %
Evaporation rate	Slower than Ether
Vapor pressure of principal solvent	4.3 hPa
Water solubility	partly miscible
Vapor density of principal solvent (Air = 1)	4
Approx. Boiling Range	125 °C
Approx. Freezing Range	Not applicable.
Gallon Weight (lbs/gal)	8.48
Specific Gravity	1.02

## SAFETY DATA SHEET

7985S v3.0  
en/US



Percent Volatile By Volume	50.10%	
Percent Volatile By Weight	42.52%	
Percent Solids By Volume	49.90%	
Percent Solids By Weight	57.48%	
pH (waterborne systems only)	not applicable	
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	377 °C	DIN 51794
Decomposition temperature	Not applicable.	
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	3.6	
VOC* as packaged (lbs/gal)	3.6	

\* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

## 10. Stability and reactivity

### Stability

Stable

### Conditions to avoid

Stable under recommended storage conditions.

### Materials to avoid

Keep away from oxidising agents and strongly acid or alkaline materials. Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO<sub>2</sub>. Evolution of CO<sub>2</sub> in closed containers causes overpressure and produces a risk of bursting.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen as well as hydrogen cyanide, amines, alcohols and water.

### Hazardous Polymerization

Will not occur.

### Sensitivity to Static Discharge

Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

### Sensitivity to Mechanical Impact

None known.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

#### Ingestion

May result in gastrointestinal distress.

## SAFETY DATA SHEET

7985S v3.0  
en/US



### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

not hazardous

#### Acute dermal toxicity

not hazardous

#### Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

### Skin corrosion/irritation

Butyl acetate	Category 3
Xylene	Category 2
Ethyl 3-ethoxy propionate	Category 3

### Serious eye damage/eye irritation

Xylene Category 2A

### Respiratory sensitisation

Not classified according to GHS criteria

### Skin sensitisation

Aliphatic polyisocyanate resin Category 1

### Germ cell mutagenicity

Not classified according to GHS criteria

### Carcinogenicity

Not classified according to GHS criteria

### Toxicity for reproduction

Not classified according to GHS criteria

### Target Organ Systemic Toxicant - Single exposure

- **Inhalation**

**airway sensitivity** Methyl amyl ketone

**Narcotic effects** Methyl amyl ketone

- **Ingestion**

**Respiratory tract irritation** Methyl amyl ketone

**Narcotic effects** Methyl amyl ketone

## SAFETY DATA SHEET

7985S v3.0  
en/US



### Target Organ Systemic Toxicant - Repeated exposure

No data available.

### Aspiration toxicity

Not classified according to GHS criteria

### Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )

No information available.

### Symptoms related to the physical, chemical and toxicological characteristics

Based on the properties of the isocyanate components and considering toxicological data on similar products, the following applies: This formulation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Components of the product may be absorbed into the body through the skin.

### Whether the hazardous chemical is listed by NTP, IARC or OSHA

Ethylbenzene IARC 2B

## 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

## 13. Disposal considerations

### Waste Disposal Method

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

## 14. Transport information

### International transport regulations

#### IMDG (Sea transport)

UN number: 1263  
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: III  
Marine Pollutant: no

#### ICAO/IATA (Air transport)

UN number: 1263  
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: III



**SAFETY DATA SHEET**7985S v3.0  
en/US**DOT**UN number: 1263  
Proper shipping name: PAINT RELATED MATERIALHazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: III  
Marine Pollutant: no  
EmS: F-E,S-E**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

**15. Regulatory information****TSCA Status**

In compliance with TSCA Inventory requirements for commercial purposes.

**DSL Status**

All components of the mixture are listed on the DSL.

**Photochemical Reactivity**

Photochemically reactive

**US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**Regulatory information**

CAS #	Ingredient	EPCRA					313	GERCLA RQ(lbs)	CAA HAP
		302	TPQ	RQ	311/312	313			
28182-81-2	Aliphatic polyisocyanate resin	N	NR	NR	A,C,R	N	NR	N	
123-86-4	Butyl acetate	N	NR	NR	A,C,F	N	NR	N	
1330-20-7	Xylene	N	NR	NR	A,C,F	Y	100	Y	
110-43-0	Methyl amyl ketone	N	NR	NR	A,C,F	N	NR	N	
100-41-4	Ethylbenzene	N	NR	NR	A,C,F	Y	1,000	Y	
763-69-9	Ethyl 3-ethoxy propionate	N	NR	NR	NA	N	NR	N	

**Key:**

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)
302	Extremely hazardous substances
311/312 Categories	F = Fire Hazard R = Reactivity Hazard P = Pressure Related Hazard A = Acute Hazard C = Chronic Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.

## SAFETY DATA SHEET

7985S v3.0  
en/US



HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available
NR	not regulated

## 16. Other information

HMIS rating H: 3 F: 3 R: 1

### Glossary of Terms:

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit.
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

### Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

Version	Changes
3.0	2, 8, 11, 15

Revision Date: 2016-01-29

**(855) 6-AXALTA**  
**cromax.us**

axalta.us

