

**SAFETY DATA SHEET**

Y32035 v3.0

en/US



## 1. Identification of the substance/mixture and of the company/undertaking

<b>Product name</b>	Thinner	
<b>Product code</b>	Y32035	Formula Date: 1999-02-11
<b>Intended use</b>	Thinner for professional use	
	Axalta Coating Systems, LLC Applied Corporate Center 50 Applied Bank Boulevard, Suite 300 US Glen Mills, PA 19342	
<b>Telephone</b>	Product information	(855) 6-AXALTA
	Medical emergency	(855) 274-5698
	Transportation emergency	(800) 424-9300 (CHEMTREC)

## 2. Hazards identification

This preparation is hazardous per the following GHS criteria

### GHS-Classification

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2A
Target Organ Systemic Toxicant - Single exposure	Category 3

Endpoints which are "not classified", "cannot classified" and "not applicable" are not shown.

### GHS-Labeling

Hazard symbols



Signal word

Danger

Hazard statements

Highly flammable liquid and vapour.  
May cause drowsiness or dizziness.  
Causes serious eye irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Wear protective gloves/ eye protection/ face protection.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ vapours/ spray.  
Use only outdoors or in a well-ventilated area.  
Wear eye protection/ face protection.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Dispose of contents/container in accordance with local regulations.

## SAFETY DATA SHEET

Y32035 v3.0  
en/US



### Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

### The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

## 3. Composition/information on ingredients

mixture of solvents

### Components

CAS-No.	Chemical Name	Concentration
78-93-3	Methyl ethyl ketone	92 - 100%
141-78-6	Ethyl acetate	1 - 4%

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Non-regulated ingredients 0.0 - 0.1%

OSHA Hazardous: Yes

## 4. First aid measures

### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

### Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

### Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

### Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

### Most Important Symptoms/effects, acute and delayed

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

**Indication of Immediate medical attention and special treatment needed if necessary**

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

**Suitable extinguishing media**

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

**Extinguishing media which shall not be used for safety reasons**

High volume water jet

**Hazardous combustion products**

CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

**Fire and Explosion Hazards**

Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

**Special Protective Equipment and Fire Fighting Procedures**

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## 6. Accidental release measures

**Procedures for cleaning up spills or leaks**

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

**Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

## 7. Handling and storage

**Precautions for safe handling**

Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY IGNITE EXPLOSIVELY. Vapors may spread long distances. Prevent buildup of vapors. Extinguish all pilot lights and turn off heaters, non-explosion proof electrical equipment and other sources of ignition during and after use and until all vapors are gone. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F).

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

**Advice on protection against fire and explosion**

Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

**Storage**

**SAFETY DATA SHEET**

Y32035 v3.0

en/US

**Requirements for storage areas and containers**

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**Advice on common storage**

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IB

## 8. Exposure controls/personal protection

**Engineering controls and work practices**

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**National occupational exposure limits**

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
78-93-3	Methyl ethyl ketone	ACGIH	8 hr	TWA	200 ppm	
		OSHA	8 hr	TWA	200 ppm	
		Dupont	8 & 12 hour	TWA	200 ppm	
141-78-6	Ethyl acetate	ACGIH	8 hr	TWA	400 ppm	
		OSHA	8 hr	TWA	400 ppm	

\*\* TWA = Time-weighted average.

**Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Respiratory protection**

Do not breathe vapors or mists. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A) during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air-purifying respirator fit is not possible, wear a positive pressure, supplied-air respirator (NIOSH TC-19C). In all cases, follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area.

**Eye protection**

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

**Skin and body protection**

Neoprene gloves and coveralls are recommended.

**Hygiene measures**

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Environmental exposure controls**

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

**SAFETY DATA SHEET**

Y32035 v3.0

en/US



## 9. Physical and chemical properties

**Appearance**

Form: liquid    Colour: clear    Odour: Characteristic Solvent Odor

Flash point	5 °F	
Lower Explosive Limit	1 %	
Upper Explosive Limit	11 %	
Evaporation rate	Slower than Ether	
Vapor pressure of principal solvent	100.9 hPa	
Water solubility	appreciable	
Vapor density of principal solvent (Air = 1)	2.5	
Approx. Boiling Range	78 °C	
Approx. Freezing Range	Not applicable.	
Gallon Weight (lbs/gal)	6.67	
Specific Gravity	0.80	
Percent Volatile By Volume	100.00%	
Percent Volatile By Weight	100.00%	
Percent Solids By Volume	0.00%	
Percent Solids By Weight	0.00%	
pH (waterborne systems only)	No data available.	
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	404 °C	DIN 51794
Decomposition temperature	Not applicable.	
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	6.7	
VOC* as packaged (lbs/gal)	6.7	

\* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

## 10. Stability and reactivity

**Stability**

Stable

**Conditions to avoid**

Stable under recommended storage conditions.

**Materials to avoid**

None reasonably foreseeable.

**Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

**Hazardous Polymerization**

Will not occur.

**Sensitivity to Static Discharge**

Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

**Sensitivity to Mechanical Impact**

None known.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

Not classified according to GHS criteria

#### Acute dermal toxicity

not hazardous

#### Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

#### Skin corrosion/irritation

Not classified according to GHS criteria

#### Serious eye damage/eye irritation

Methyl ethyl ketone	Category 2A
Ethyl acetate	Category 2A

#### Respiratory sensitisation

Not classified according to GHS criteria

#### Skin sensitisation

not hazardous

#### Germ cell mutagenicity

not hazardous

#### Carcinogenicity

Not classified according to GHS criteria

#### Toxicity for reproduction

Not classified according to GHS criteria

## SAFETY DATA SHEET

Y32035 v3.0

en/US



### Target Organ Systemic Toxicant - Single exposure

- **Inhalation**

**reproductive organs** Ethyl acetate

### Target Organ Systemic Toxicant - Repeated exposure

not hazardous

### Aspiration toxicity

Not classified according to GHS criteria

### Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )

No information available.

### Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

Whether the hazardous chemical is listed by NTP, IARC or OSHA

## 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

## 13. Disposal considerations

### Waste Disposal Method

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

## 14. Transport information

### International transport regulations

#### IMDG (Sea transport)

UN number: 1263  
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: II  
Marine Pollutant: no

#### ICAO/IATA (Air transport)

UN number: 1263  
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3

**SAFETY DATA SHEET**

Y32035 v3.0

en/US



Subsidiary Hazard Class: Not applicable.  
Packing group: II

**DOT**

UN number: 1263  
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: II  
Marine Pollutant: no  
EmS: F-E,S-E

**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

**15. Regulatory information****TSCA Status**

In compliance with TSCA Inventory requirements for commercial purposes.

**DSL Status**

All components of the mixture are listed on the DSL.

**Photochemical Reactivity**

Non-photochemically reactive

**Regulatory information**

CAS #	Ingredient	EPCRA					CERCLA RQ(lbs)	CAA HAP
		302	TPQ	RQ	311/312	313		
78-93-3	Methyl ethyl ketone	N	NR	NR	A,C,F	N	5,000	N
141-78-6	Ethyl acetate	N	NR	NR	C,F	N	NR	N

**Key:**

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)
302	Extremely hazardous substances
311/312 Categories	F = Fire Hazard                      A = Acute Hazard R = Reactivity Hazard                C = Chronic Hazard P = Pressure Related Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available
NR	not regulated



## SAFETY DATA SHEET

Y32035 v3.0

en/US



## 16. Other information

HMIS rating H: 2 F: 3 R: 0

Glossary of Terms:

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit.
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

### Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

Version	Changes
3.0	2, 8

Revision Date: 2016-01-15

**(855) 6-AXALTA**  
**axalta.us**

