Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:



#### 1. Identification

Product identifier used on the label:

Product Name: Everglass quart

Product identifier: 100632

Other means of identification

**Synonyms:** No data available

Recommended use of the chemical and restrictions on

Fiberglass reinforced bodyfiller

use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer / ITW Evercoat

**Importer / Distributor:** a division of Illinois Tool Works Inc.

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

#### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





**GHS Classification:** Respiratory Sensitisation Category 1

Skin Sensitisation Category 1
Reproductive Toxicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Germ Cell Mutagenicity Category 2

Carcinogenicity Category 2 Flammable Liquid Category 3

Hazardous to the aquatic environment - Acute Category 3

GHS Signal Word: Danger

Page **1** of **10** 

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

**GHS Hazard Statements:** Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing genetic defects.

Suspected of causing cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

**GHS Precautionary Statements:** Safety Precautions:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Wear respiratory protection.

**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction.

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

**Storage:** Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

Reports have associated repeated and prolonged occupational overexposure to

classified:

solvents with permanent brain and nervous system damage.

### 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient	
Styrene	100-42-5	10 - 30	
Acid anhydride	85-43-8	0.1 - 1	
Dimethylaniline (DMA)	121-69-7	0.1 - 1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower

eye lids. Seek immediate medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation

develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing

before reuse.

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably

on a doctor's advice.

**Ingestion:** Do not induce vomiting and seek medical attention immediately.

Page 3 of 10

**Product Name: Everglass quart Product identifier:** 100632 **Revision Date:** 03-18-2016

Replaces:

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Most important symptoms/effects, acute and delayed:

Most important

No data available

symptoms/effects (Acute):

Most important

No data available

symptoms/effects (Delayed):

Indication of immediate medical attention and special treatment

No additional first aid information available

needed, if necessary:

### 5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water

> spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Regular foam Carbon dioxide Dry

chemical

No data available Unsuitable extinguishing media:

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion

Hazards:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition

and flash back.

**Hazardous Combustion** 

**Products:** 

Carbon dioxide, Carbon monoxide, Styrene oxide, Phthalic

anhydride, Hydrocarbons

Special protective equipment and precautions for fire-

fighters:

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the

potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

with appropriate turn-out gear and chemical resistant personal protective equipment.

#### 6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Methods and materials for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

No special spill clean-up considerations. Collect and discard in

regular trash. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid

breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

#### 7. Handling and storage

**Precautions for safe handling:** Mildly irritating material. Avoid unnecessary exposure. All hazard

precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the

reach of children.

Conditions for safe storage, including any incompatibilities

**Conditions for safe storage:** Store in a cool dry place. Isolate from incompatible materials. Store

in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact

with incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Peroxides Strong acids Strong oxidizing agents Polymerization

catalysts

#### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	
Styrene	ne 100 ppm		40 ppm STEL; 170 mg/m3	
			STEL	

Appropriate engineering

No exposure limits exist for the constituents of this product. Use

**Product Name: Everglass quart Product identifier:** 100632 **Revision Date:** 03-18-2016

Replaces:

controls: local exhaust ventilation or other engineering controls to minimize

> exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust

ventilation should be used.

Individual protection measures, such as personal protective equipment:

**Eye Protection:** Wear chemically resistant safety glasses with side shields when

> handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of

product.

Skin Protection: Not normally considered a skin hazard. Where use can result in skin

> contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin

contact, wear impervious clothing and boots

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure

> when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate

matter and organic solvent vapors.

Splash proof chemical goggles are recommended to protect against Other Protective Equipment:

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin

contact, wear impervious clothing and boots

All hazard precautions given in the data sheet must be observed. **General Hygiene Conditions:** 

> Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of

the reach of children.

### 9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state): Paste Color: Blue/Green Odor: Aromatic

Odor threshold: No data available

pH: Neutral

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C): 145 Flash Point (°C): 49

**Evaporation Rate:**No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive limits:
Upper Flammable/Explosive Limit: 6.1
Lower Flammable/Explosive Limit: 1.1

**Vapor Pressure:** 5 MMHG@20C/68F

**Vapor Density:** Heavier than air. Vapors that evolve from this product

will tend to settle and accumulate near the floor.

Relative Density: 1.71
Solubility(ies): Insoluble
Partition coefficient: n-octanol/water: 1.36
Auto-ignition Temperature (°C): 490 °C

Viscosity:No data availableVOC (as packaged-less exempts and water)1.05 or 127VOC (as applied\*- 2% by wt hardener-less0.52 or 62

exempts and water)

Percent Solids by weight – as packaged 92.60 Percent Solids by weight – as applied\* - 2% 96.30

by wt hardener

VHAP Content by weight – as packaged 12.1 VHAP Content by weight – as applied\* - 2% 5.9

by weight hardener

#### 10. Stability and reactivity

**Reactivity:** No data available

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous**No data available

reactions:

Conditions to avoid (e.g., static None known. .

discharge, shock, or vibration):

**Incompatible materials:** Peroxides Strong acids Strong oxidizing agents Polymerization

catalysts

Hazardous decomposition

products:

Carbon dioxide Carbon monoxide Styrene oxide Hydrocarbons

### 11. Toxicological information

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

Information on the likely routes

Ingestion, Skin contact, Eye contact, Absorption

of exposure (inhalation,

ingestion, skin and eye contact):

Symptoms related to the

No data available

physical, chemical and toxicological characteristics:

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

**Inhalation Irritation:** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Excessive inhalation of vapors may cause nasal and respiratory irritation,

acute nervous system depression, fatigue, weakness, nausea, headache and

dizziness.

Airborne overexposure well above the PEL may result additionally in eye irritation,

headache, chemical bronchitis, asthma-like findings or pulmonary edema.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Skin Absorption:** No absorption hazard in normal industrial use. Causes skin irritation. Contact may

cause irritation and possible dermatitis or sensitization. Symptoms may include

redness, burning, drying and cracking of skin, and skin burns

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue. Contact with liquid or vapor may result in irritation, redness,

tearing, and blurred vision.

**Ingestion Irritation:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into

the lungs can cause chemical pneumonitis which can be fatal.

**Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning.

**Long-Term (Chronic) Health Effects:** 

Carcinogenicity: The International Agency for Research on Cancer (IARC) has classified styrene as a

group 2B carcinogen (possibly carcinogenic to humans).

Reproductive and

May damage fertility or the unborn child.

**Developmental Toxicity:** 

**Mutagenicity:** Suspected of causing genetic defects.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatique, nausea and headache.

**Skin Contact:** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

**Skin Absorption:** Upon prolonged or repeated exposure, no hazard in normal industrial use.

Numerical measures of toxicity (such as acute toxicity estimates)

**Component Toxicology Data** 

Chemical Component	Chemical Component Oral LD50		Inhalation LC50	
No data available				

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
Styrene	N	Υ	Υ	

### 12. Ecological information

**Ecotoxicity (aquatic and**Toxic to aquatic life. Styrene is toxic to aquatic organisms and should

terrestrial, where available): not be released

to sewage, draining systems or any body of water exceeding

concentrations of approved limits under applicable regulations and

permits.

Persistence and degradability: No data available

**Bioaccumulative potential:** No data

Mobility in soil:

Other adverse effects (such as No data available No data available

hazardous to the ozone layer):

**Ecological Toxicity Data** 

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

**Description of waste residues:** Spent or discarded material is a hazardous waste.

**Safe Handling of Waste:** This material as supplied, if discarded, would be regulated as a

hazardous waste under RCRA (40 CFR 261).

Waste treatment methods Dispose of by incineration following Federal, State, Local, or

**(including packaging):** Provincial regulations.

Waste Disposal Code(s): D001

#### 14. Transport information

UN number: UN3269

**UN proper shipping name:** POLYESTER RESIN KIT

Transport hazard class(es): 3
Packing group: |||

Product Name: Everglass quart Product identifier: 100632 Revision Date: 03-18-2016

Replaces:

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

#### 15. Regulatory information

#### Safety, health and environmental regulations specific for the product in question

**TSCA Status:** The intentional ingredients of this product are listed.

**Regulated Components:** 

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	N	N	Υ	N

### 16. Other information, including date of preparation or last revision.

**Revision Date:** 03-18-2016

Revision Number: 14

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances