

# SAFETY DATA SHEET

400-01 v6.1  
en/US



## 1. Identification of the substance/mixture and of the company/undertaking

|                     |   |                           |
|---------------------|---|---------------------------|
| <b>Product name</b> | Black   |                           |
| <b>Product code</b> | 400-01  | Formula Date: 2009-02-10  |
| <b>Intended use</b> | Coating for professional use  |                           |
|                     | Axalta Coating Systems, LLC Applied Corporate Center<br>50 Applied Bank Boulevard, Suite 300<br>US Glen Mills, PA 19342 |                           |
| <b>Telephone</b>    | Product information   | (855) 6-AXALTA            |
|                     | Medical emergency   | (855) 274-5698            |
|                     | Transportation emergency  | (800) 424-9300 (CHEMTREC) |

## 2. Hazards identification

This preparation is hazardous per the following GHS criteria

### GHS-Classification

|  |            |
|--|------------|
| Flammable liquids                                  | Category 2 |
| Skin corrosion/irritation                          | Category 2 |
| Carcinogenicity                                    | Category 2 |
| Toxicity for reproduction                          | Category 2 |
| Target Organ Systemic Toxicant - Single exposure   | Category 3 |
| Target Organ Systemic Toxicant - Repeated exposure | Category 2 |

Endpoints which are "not classified", "cannot classified" and "not applicable" are not shown.

### GHS-Labeling



Hazard symbols

Signal word Danger

Hazard statements  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
Highly flammable liquid and vapour.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
Causes skin irritation.

Precautionary statements  
Obtain special instructions before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Use only outdoors or in a well-ventilated area.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF ON SKIN: Wash with plenty of soap and water.

## SAFETY DATA SHEET

400-01 v6.1  
en/US



Specific treatment (see supplemental first aid instructions on this label).  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
Store locked up.  
Store in a well-ventilated place. Keep container tightly closed.  
Dispose of contents/container in accordance with local regulations.

### Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

### The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

## 3. Composition/information on ingredients

Mixture of synthetic resins, pigments, and solvents

### Components

| CAS-No.    | Chemical Name                           | Concentration |
|------------|---|---------------|
| 123-86-4   | Butyl acetate                           | 15 - 26%      |
| 108-88-3   | Toluene                                 | 7%            |
| 8032-32-4  | Vm&p naphtha                            | 4 - 15%       |
| 112-07-2   | Ethylene glycol monobutyl ether acetate | 3%            |
| 1330-20-7  | Xylene                                  | 3%            |
| 64742-94-5 | Aromatic hydrocarbon                    | 1 - 4%        |
| 1333-86-4  | Carbon black                            | 1.9%          |
| 763-69-9   | Ethyl 3-ethoxy propionate               | 1 - 4%        |
| 141-78-6   | Ethyl acetate                           | 1 - 4%        |
| 142-82-5   | Heptane                                 | 1 - 4%        |
| 108-10-1   | Methyl isobutyl ketone                  | 1.1%          |
| 100-41-4   | Ethylbenzene                            | 0.8%          |
| 91-20-3    | Naphthalene                             | 0.2%          |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Non-regulated ingredients 40 - 50%

OSHA Hazardous: Yes

\* Assigned CAS No. - An official CAS No. does not exist. The CAS No. shown is for a similar chemical.

## 4. First aid measures

## SAFETY DATA SHEET

400-01 v6.1  
en/US



### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

### Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

### Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

### Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

### Most Important Symptoms/effects, acute and delayed

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

### Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

### Extinguishing media which shall not be used for safety reasons

High volume water jet

### Hazardous combustion products

CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

### Fire and Explosion Hazards

Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

### Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## 6. Accidental release measures

## SAFETY DATA SHEET

400-01 v6.1  
en/US



### Procedures for cleaning up spills or leaks

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

### Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

## 7. Handling and storage

### Precautions for safe handling

Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY CAUSE FLASH FIRE. Close container after each use. Ground containers when pouring. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F). If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

### Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

### Storage

#### Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IB

## 8. Exposure controls/personal protection

### Engineering controls and work practices

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### National occupational exposure limits

| CAS-No.  | Chemical Name | Source | Time   | Type | Value   | Note |
|----------|---------------|--------|--------|------|---------|------|
| 123-86-4 | Butyl acetate | ACGIH  | 15 min | STEL | 200 ppm |      |
|          |               |        | 8 hr   | TWA  | 150 ppm |      |
|          |               | OSHA   | 8 hr   | TWA  | 150 ppm |      |
| 108-88-3 | Toluene       | OSHA   |        | CEIL | 300 ppm |      |
|          |               |        | 10 min | TWA  | 500 ppm |      |

## SAFETY DATA SHEET

400-01 v6.1  
en/US

| CAS-No.    | Chemical Name                           | Source | Time        | Type | Value     | Note |
|------------|---|--------|-------------|------|-----------|------|
|            |   |        | 8 hr        | TWA  | 200 ppm   |      |
|            |   | Dupont | 8 & 12 hour | TWA  | 20 ppm    | Skin |
| 8032-32-4  | Vm&p naphtha                            | ACGIH  | 8 hr        | TWA  | 300 ppm   |      |
|            |   | Dupont | 8 hr        | TWA  | 100 ppm   |      |
| 112-07-2   | Ethylene glycol monobutyl ether acetate | ACGIH  | 8 hr        | TWA  | 20 ppm    |      |
|            |   | Dupont | 8 & 12 hour | TWA  | 20 ppm    |      |
| 1330-20-7  | Xylene                                  | ACGIH  | 15 min      | STEL | 150 ppm   |      |
|            |   |        | 8 hr        | TWA  | 100 ppm   |      |
|            |   | OSHA   | 8 hr        | TWA  | 100 ppm   |      |
|            |   | Dupont | 8 & 12 hour | TWA  | 100 ppm   |      |
| 64742-94-5 | Aromatic hydrocarbon                    | Dupont | 8 & 12 hour | TWA  | 100 ppm   |      |
| 1333-86-4  | Carbon black                            | ACGIH  | 8 hr        | TWA  | 3 mg/m3   |      |
|            |   | OSHA   | 8 hr        | TWA  | 3.5 mg/m3 |      |
|            |   | Dupont | 8 & 12 hour | TWA  | 0.5 mg/m3 |      |
| 141-78-6   | Ethyl acetate                           | ACGIH  | 8 hr        | TWA  | 400 ppm   |      |
|            |   | OSHA   | 8 hr        | TWA  | 400 ppm   |      |
| 142-82-5   | Heptane                                 | ACGIH  | 15 min      | STEL | 500 ppm   |      |
|            |   |        | 8 hr        | TWA  | 400 ppm   |      |
|            |   | OSHA   | 8 hr        | TWA  | 500 ppm   |      |
| 108-10-1   | Methyl isobutyl ketone                  | ACGIH  | 15 min      | STEL | 75 ppm    |      |
|            |   |        | 8 hr        | TWA  | 20 ppm    |      |
|            |   | OSHA   | 8 hr        | TWA  | 100 ppm   |      |
| 100-41-4   | Ethylbenzene                            | ACGIH  | 8 hr        | TWA  | 20 ppm    |      |
|            |   | OSHA   | 8 hr        | TWA  | 100 ppm   |      |
|            |   | Dupont | 8 & 12 hour | TWA  | 25 ppm    |      |
| 91-20-3    | Naphthalene                             | ACGIH  |             | CEIL | 15 ppm    | Skin |
|            |   |        | 8 hr        | TWA  | 10 ppm    | Skin |
|            |   | OSHA   | 8 hr        | TWA  | 10 ppm    |      |

## SAFETY DATA SHEET

400-01 v6.1  
en/US



| CAS-No. | Chemical Name | Source | Time           | Type | Value   | Note |
|---------|---------------|--------|----------------|------|---------|------|
|         |               | Dupont | 8 & 12<br>hour | TWA  | 0.1 ppm |      |

\*\* STEL = Short term exposure limit.

TWA = Time-weighted average.

CEIL = Ceiling.

### Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

### Respiratory protection

Do not breathe vapors or mists. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A) during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air-purifying respirator fit is not possible, wear a positive pressure, supplied-air respirator (NIOSH TC-19C). In all cases, follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area.

### Eye protection

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

### Skin and body protection

Neoprene gloves and coveralls are recommended.

### Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

### Environmental exposure controls

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

## 9. Physical and chemical properties

### Appearance

Form: liquid    Colour: black    Odour: Characteristic Paint Odor

|  |                   |           |
|--|-------------------|-----------|
| Flash point                                  | 50 °F             |           |
| Lower Explosive Limit                        | 0.9 %             |           |
| Upper Explosive Limit                        | 7.5 %             |           |
| Evaporation rate                             | Slower than Ether |           |
| Vapor pressure of principal solvent          | 12.5 hPa          |           |
| Water solubility                             | moderate          |           |
| Vapor density of principal solvent (Air = 1) | 4                 |           |
| Approx. Boiling Range                        | 109 °C            |           |
| Approx. Freezing Range                       | Not applicable.   |           |
| Gallon Weight (lbs/gal)                      | 8.08              |           |
| Specific Gravity                             | 0.97              |           |
| Percent Volatile By Volume                   | 64.74%            |           |
| Percent Volatile By Weight                   | 56.65%            |           |
| Percent Solids By Volume                     | 35.26%            |           |
| Percent Solids By Weight                     | 43.35%            |           |
| pH (waterborne systems only)                 | not applicable    |           |
| Partition coefficient: n-octanol/water       | no data available |           |
| Ignition temperature                         | 215 °C            | DIN 51794 |

## SAFETY DATA SHEET

400-01 v6.1  
en/US



|                            |                 |               |
|----------------------------|-----------------|---------------|
| Decomposition temperature  | Not applicable. |               |
| Viscosity (23 °C)          | Not applicable. | ISO 2431-1993 |
| VOC* less exempt (lbs/gal) | 4.6             |               |
| VOC* as packaged (lbs/gal) | 4.6             |               |

\* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

## 10. Stability and reactivity

### Stability

Stable

### Conditions to avoid

Stable under recommended storage conditions.

### Materials to avoid

None reasonably foreseeable.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

### Hazardous Polymerization

Will not occur.

### Sensitivity to Static Discharge

Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

### Sensitivity to Mechanical Impact

None known.

## 11. Toxicological information

### Information on likely routes of exposure

#### Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

not hazardous

## SAFETY DATA SHEET

400-01 v6.1  
en/US



### Acute dermal toxicity

not hazardous

### Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

### Skin corrosion/irritation

|                           |            |
|---------------------------|------------|
| Butyl acetate             | Category 3 |
| Toluene                   | Category 2 |
| Xylene                    | Category 2 |
| Aromatic hydrocarbon      | Category 3 |
| Ethyl 3-ethoxy propionate | Category 3 |
| Ethyl acetate             | Category 3 |
| Heptane                   | Category 2 |
| Methyl isobutyl ketone    | Category 3 |

### Serious eye damage/eye irritation

Not classified according to GHS criteria

### Respiratory sensitisation

Not classified according to GHS criteria

### Skin sensitisation

Not classified according to GHS criteria

### Germ cell mutagenicity

Not classified according to GHS criteria

### Carcinogenicity

Naphthalene Category 2

### Toxicity for reproduction

Toluene Category 2

### Target Organ Systemic Toxicant - Single exposure

- Skin Absorption

**Narcotic effects** Toluene

- Inhalation

**Central nervous system** Vm&p naphtha

**reproductive organs** Ethyl acetate, Heptane

### Target Organ Systemic Toxicant - Repeated exposure

- Skin Absorption

**Body weight effects** Ethyl acetate



## SAFETY DATA SHEET

400-01 v6.1  
en/US



### Aspiration toxicity

Not classified according to GHS criteria

### Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )

No information available.

### Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

### Whether the hazardous chemical is listed by NTP, IARC or OSHA

|                        |                 |
|------------------------|-----------------|
| Carbon black           | IARC 2B         |
| Methyl isobutyl ketone | IARC 2B         |
| Ethylbenzene           | IARC 2B         |
| Naphthalene            | IARC 2B         |
| Naphthalene            | NTP Anticipated |

## 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

## 13. Disposal considerations

### Waste Disposal Method

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

## 14. Transport information

### International transport regulations

#### IMDG (Sea transport)

|                          |                                    |
|--------------------------|------------------------------------|
| UN number:               | 1263                               |
| Proper shipping name:    | PAINT                              |
| Hazard Class:            | 3                                  |
| Subsidiary Hazard Class: | Not applicable.                    |
| Packing group:           | II                                 |
| Marine Pollutant:        | yes [heptane (mixture of isomers)] |

#### ICAO/IATA (Air transport)

|                          |                 |
|--------------------------|-----------------|
| UN number:               | 1263            |
| Proper shipping name:    | PAINT           |
| Hazard Class:            | 3               |
| Subsidiary Hazard Class: | Not applicable. |
| Packing group:           | II              |

#### DOT

|                       |       |
|-----------------------|-------|
| UN number:            | 1263  |
| Proper shipping name: | PAINT |

**SAFETY DATA SHEET**400-01 v6.1  
en/US

Hazard Class: 3  
 Subsidiary Hazard Class: Not applicable.  
 Packing group: II  
 Marine Pollutant: yes [heptane (mixture of isomers)]  
 EmS: F-E,S-E

**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

**15. Regulatory information****TSCA Status**

In compliance with TSCA Inventory requirements for commercial purposes.

**DSL Status**

All components of the mixture are listed on the DSL.

**Photochemical Reactivity**

Photochemically reactive

**US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)**

WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects, or other reproductive harm.

**Regulatory information**

| CAS #      | Ingredient                              | EPCRA |     |    |           |     | CERCLA<br>RQ(lbs) | CAA<br>HAP |
|------------|---|-------|-----|----|-----------|-----|-------------------|------------|
|            |   | 302   | TPQ | RQ | 311/312   | 313 |                   |            |
| 123-86-4   | Butyl acetate                           | N     | NR  | NR | A,C,F     | N   | NR                | N          |
| 108-88-3   | Toluene                                 | N     | NR  | NR | A,C,F     | Y   | 1,000             | Y          |
| 8032-32-4  | Vm&p naphtha                            | N     | NR  | NR | A,C,F     | N   | NR                | N          |
| 112-07-2   | Ethylene glycol monobutyl ether acetate | N     | NR  | NR | A,C,F     | Y   | NR                | Y          |
| 1330-20-7  | Xylene                                  | N     | NR  | NR | A,C,F     | Y   | 100               | Y          |
| 64742-94-5 | Aromatic hydrocarbon                    | N     | NR  | NR | A         | N   | NR                | N          |
| 1333-86-4  | Carbon black                            | N     | NR  | NR | C         | N   | NR                | N          |
| 763-69-9   | Ethyl 3-ethoxy propionate               | N     | NR  | NR | NA        | N   | NR                | N          |
| 141-78-6   | Ethyl acetate                           | N     | NR  | NR | C,F       | N   | NR                | N          |
| 142-82-5   | Heptane                                 | N     | NR  | NR | A,C,F     | N   | NR                | N          |
| 108-10-1   | Methyl isobutyl ketone                  | N     | NR  | NR | A,C,F,N,R | Y   | 5,000             | Y          |
| 100-41-4   | Ethylbenzene                            | N     | NR  | NR | A,C,F     | Y   | 1,000             | Y          |
| 91-20-3    | Naphthalene                             | N     | NR  | NR | A,C,F     | Y   | 100               | Y          |

**Key:**

|                    |  |
|--------------------|--|
| EPCRA              | Emergency Planning and Community Right-to-know Act (aka Title III, SARA)   |
| 302                | Extremely hazardous substances   |
| 311/312 Categories | F = Fire Hazard<br>R = Reactivity Hazard<br>P = Pressure Related Hazard  |
|                    | A = Acute Hazard<br>C = Chronic Hazard   |
| 313 Information    | Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of |

**SAFETY DATA SHEET**

400-01 v6.1  
en/US



|        |  |
|--------|--|
|        | Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372. |
| CERCLA | Comprehensive Emergency Response, Compensation and Liability Act of 1980.                        |
| HAP    | Listed as a Clean Air Act Hazardous Air Pollutant.   |
| TPQ    | Threshold Planning Quantity.   |
| RQ     | Reportable Quantity  |
| NA     | not available  |
| NR     | not regulated  |

**16. Other information**

HMIS rating H: 2 F: 3 R: 0

Glossary of Terms:

|       |  |
|-------|--|
| ACGIH | American Conference of Governmental Industrial Hygienists. |
| IARC  | International Agency for Research on Cancer.               |
| NTP   | National Toxicology Program.                               |
| OEL   | Occupational Exposure Limit                                |
| OSHA  | Occupational Safety and Health Administration.             |
| STEL  | Short term exposure limit.                                 |
| TWA   | Time-weighted average.                                     |
| PNOR  | Particles not otherwise regulated.                         |
| PNOC  | Particles not otherwise classified.                        |

NOTE: The list (above) of glossary terms may be modified.

Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

| Version | Changes |
|---------|---------|
| 6.1     | 2, 15   |

Revision Date: 2016-01-29

**(855) 6-AXALTA**  
**nasonfinishes.us**

axalta.us

