

Ful-Thane® 401-20™ 2K Urethane Integrated Clear



GENERAL

DESCRIPTION

Designed to enhance the depth and color of Ful-Thane® factory packaged colors, Ful-Thane® 2K Urethane single-stage colors and Ful-Cryl® II mix colors.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Ful-Thane® 401-20™ 2K Urethane Integrated Clear
 Ful-Thane® 2K 483-15™ 2K Urethane Activator
 Ful-Base® 441-20™ Reducer (Low-Temp)
 Ful-Base® 441-21™ Reducer (Mid-Temp)
 Ful-Base® 441-22™ Reducer (High-Temp)

MIX RATIO

Combine the components by volume (8:1:2). Mix thoroughly prior to activation.

Component	Volume
Ful-Thane® 401-20™ 2K Urethane Integrated Clear	8
Ful-Thane® 2K 483-15™ 2K Urethane Activator	1
Ful-Base® 441-20™ / 441-21™ / 441-22™ Reducer	2

Then add equal part activator and reduced Ful-Thane® or Ful-Cryl® II color (for final color coat only).

VISCOSITY

16-19" #2 Zahn

POT LIFE

4 hours at 70°F (21°C)



APPLICATION

APPLICATION

On the final color coat, apply integrated clear and color mixture following Ful-Thane® or Ful-Cryl® II label directions.

CLEANING OF PAINT EQUIPMENT

Clean spray equipment as soon as possible with lacquer thinner or low VOC cleaner in VOC regulated markets.

IMPORTANT NOTES

- Do not use as a topcoat clear
- Use as an integrated clear in final coat only
- Be certain clear and color are properly catalyzed and reduced



DRY TIMES

Refer to Ful-Thane® or Ful-Cryl® II TDS for information.



PHYSICAL PROPERTIES

All Values Ready To Spray

Max. VOC (LE):	4.8 lbs./gal (570 g/L)
Max. VOC (AP):	4.7 lbs./gal (561 g/L)
Avg. Gal. Wt.:	7.96 lbs./gal (954 g/L)
Avg. Wt.% Volatiles:	59.7%
Avg. Wt.% Exempt Solvent:	2.9%
Avg. Wt.% Water:	0.0%
Avg. Vol.% Exempt Solvent:	3.5%
Avg. Vol.% Water:	0.0%
Theoretical Coverage:	483 ft ² (44.9 m ²) at 1 mil
Recommended Dry Film Thickness:	2.0 mils in 2 coats
Flash Point:	See SDS/MSDS

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS/MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: May 2015

In the United States:
1.855.6.AXALTA
nasonfinishes.com

In Canada:
1.800.668.6945
nasonfinishes.ca

