

**1 Identification**

- **Product identifier**
- **Trade name:** XXX Specialty Gel Adhesive Remover
- **Article number:** 77793
- **Application of the substance / the mixture** Exterior vehicle cleaner
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803-207-8225
- **Information department:**  
cust\_care@semproducts.com, 1685 Overview Dr. Rock Hill SC 29730; phone 1-800-831-1122, M-Th 7am-4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 1)

· Hazard pictograms



· Signal word *Danger*

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light aliph. acetone

· Hazard statements

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.

· Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 2)

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.\* **3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

|            |   |        |
|------------|---|--------|
| 67-64-1    | acetone                                   | 30-40% |
| 1330-20-7  | xylene                                    | 13-30% |
| 64742-89-8 | Solvent naphtha (petroleum), light aliph. | 13-30% |
| 68476-86-8 | Petroleum gases, liquefied, sweetened     | 7-10%  |

\* **4 First-aid measures**· **Description of first aid measures**· **General information:** Immediately remove any clothing soiled by the product.· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

\* **5 Fire-fighting measures**· **Extinguishing media**· **Suitable extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

|           |                  |                       |
|-----------|------------------|-----------------------|
| 67-64-1   | acetone          | 200 ppm               |
| 1330-20-7 | xylene           | 130 ppm               |
| 123-86-4  | n-butyl acetate  | 5 ppm                 |
| 7447-41-8 | lithium chloride | 2.3 mg/m <sup>3</sup> |

· **PAC-2:**

|           |                  |                      |
|-----------|------------------|----------------------|
| 67-64-1   | acetone          | 3200* ppm            |
| 1330-20-7 | xylene           | 920* ppm             |
| 123-86-4  | n-butyl acetate  | 200 ppm              |
| 7447-41-8 | lithium chloride | 25 mg/m <sup>3</sup> |

· **PAC-3:**

|           |                  |                       |
|-----------|------------------|-----------------------|
| 67-64-1   | acetone          | 5700* ppm             |
| 1330-20-7 | xylene           | 2500* ppm             |
| 123-86-4  | n-butyl acetate  | 3000* ppm             |
| 7447-41-8 | lithium chloride | 150 mg/m <sup>3</sup> |

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

|     |  |
|-----|--|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm   |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm   |
| TLV | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 594 mg/m <sup>3</sup> , 250 ppm |
| BEI |  |

### 1330-20-7 xylene

|     |   |
|-----|---|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm |
| BEI |   |

- **Ingredients with biological limit values:**

### 67-64-1 acetone

|     |  |
|-----|--|
| BEI | 50 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
|-----|--|

### 1330-20-7 xylene

|     |  |
|-----|--|
| BEI | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----|--|

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

(Contd. on page 6)

**Trade name: XXX Specialty Gel Adhesive Remover**

(Contd. of page 5)

Store protective clothing separately.

Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Safety glasses



Tightly sealed goggles

**9 Physical and chemical properties****· Information on basic physical and chemical properties****· General Information****· Appearance:**

|                        |                                    |
|------------------------|------------------------------------|
| <b>Form:</b>           | Aerosol                            |
| <b>Color:</b>          | According to product specification |
| <b>Odor:</b>           | Characteristic                     |
| <b>Odor threshold:</b> | Not determined.                    |

**· pH-value:** Not determined.

**· Change in condition**

|                                     |               |
|-------------------------------------|---------------|
| <b>Melting point/Melting range:</b> | Undetermined. |
| <b>Boiling point/Boiling range:</b> | 55.8-56.6 °C  |

**· Flash point:** -103 °C

**· Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:** 500 °C

**· Decomposition temperature:** Not determined.

**· Auto igniting:** Product is not selfigniting.

(Contd. on page 7)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 6)

|   |   |
|---|---|
| · <b>Danger of explosion:</b>                     | <i>In use, may form flammable/explosive vapour-air mixture.</i> |
| · <b>Explosion limits:</b>                        |   |
| <b>Lower:</b>                                     | <i>1.1 Vol %</i>  |
| <b>Upper:</b>                                     | <i>9.5 Vol %</i>  |
| · <b>Vapor pressure at 20 °C:</b>                 | <i>14 hPa</i>   |
| · <b>Density at 20 °C:</b>                        | <i>0.76163 g/cm<sup>3</sup></i>                                 |
| · <b>Relative density</b>                         | <i>Not determined.</i>  |
| · <b>Vapor density</b>                            | <i>Not determined.</i>  |
| · <b>Evaporation rate</b>                         | <i>Not applicable.</i>  |
| · <b>Solubility in / Miscibility with Water:</b>  | <i>Not miscible or difficult to mix.</i>                        |
| · <b>Partition coefficient (n-octanol/water):</b> | <i>Not determined.</i>  |
| · <b>Viscosity:</b>                               |   |
| <b>Dynamic:</b>                                   | <i>Not determined.</i>  |
| <b>Kinematic:</b>                                 | <i>Not determined.</i>  |
| · <b>Solvent content:</b>                         |   |
| <b>Organic solvents:</b>                          | <i>99.8 %</i>   |
| <b>VOC content:</b>                               | <i>67.93 %</i>  |
|   | <i>746.5 g/l / 6.23 lb/gal</i>                                  |
| · <b>Solids content:</b>                          | <i>0.2 %</i>  |
| · <b>Other information</b>                        | <i>No further relevant information available.</i>               |

## 10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **on the skin:** *Irritant to skin and mucous membranes.*
- **on the eye:** *Irritating effect.*
- **Sensitization:** *No sensitizing effects known.*

(Contd. on page 8)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

|           |        |   |
|-----------|--------|---|
| 1330-20-7 | xylene | 3 |
|-----------|--------|---|

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

\* **12 Ecological information**· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Not hazardous for water.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

\* **13 Disposal considerations**· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

\* **14 Transport information**· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1950

· **UN proper shipping name**· **DOT**

Aerosols, flammable

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

(Contd. on page 9)

USA



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1  
· **Label** 2.1

· **ADR**



· **Class** 2.5F Gases  
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
· **Label** 2.1

· **Packing group**  
· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases  
· **EMS Number:** F-D,S-U  
· **Stowage Code** SW1 Protected from sources of heat.  
SW2 Clear of living quarters.  
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg

(Contd. on page 10)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 9)

|  |  |
|--|--|
| · <b>ADR</b><br>· <b>Excepted quantities (EQ)</b>                                      | Code: E0<br>Not permitted as Excepted Quantity       |
| · <b>IMDG</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b> | IL<br>Code: E0<br>Not permitted as Excepted Quantity |
| · <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1                                |

**15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
· Sara

|  |
|--|
| · <b>Section 355 (extremely hazardous substances):</b> |
| None of the ingredient is listed.                      |

|  |
|--|
| · <b>Section 313 (Specific toxic chemical listings):</b> |
| 1330-20-7   xylene                                       |

|  |        |
|--|--------|
| · <b>TSCA (Toxic Substances Control Act):</b>      |        |
| 67-64-1   acetone                                  | ACTIVE |
| 1330-20-7   xylene                                 | ACTIVE |
| 68476-86-8   Petroleum gases, liquefied, sweetened | ACTIVE |
| 123-86-4   n-butyl acetate                         | ACTIVE |
| 7447-41-8   lithium chloride                       | ACTIVE |

|                                   |
|-----------------------------------|
| · <b>Hazardous Air Pollutants</b> |
| 1330-20-7   xylene                |

· **Proposition 65**

|   |
|---|
| · <b>Chemicals known to cause cancer:</b> |
| None of the ingredients is listed.        |

|  |
|--|
| · <b>Chemicals known to cause reproductive toxicity for females:</b> |
| None of the ingredients is listed.                                   |

|  |
|--|
| · <b>Chemicals known to cause reproductive toxicity for males:</b> |
| None of the ingredients is listed.                                 |

|   |
|---|
| · <b>Chemicals known to cause developmental toxicity:</b> |
| 1330-20-7   xylene  |

· **Carcinogenicity categories**

|  |   |
|--|---|
| · <b>EPA (Environmental Protection Agency)</b> |   |
| 67-64-1   acetone                              | I |
| 1330-20-7   xylene                             | I |

|   |    |
|---|----|
| · <b>TLV (Threshold Limit Value established by ACGIH)</b> |    |
| 67-64-1   acetone   | A4 |
| 1330-20-7   xylene  | A4 |

(Contd. on page 11)



Trade name: XXX Specialty Gel Adhesive Remover

(Contd. of page 10)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
acetone

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P302+P352 If on skin: Wash with plenty of water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a poison center/doctor if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)

**Trade name: XXX Specialty Gel Adhesive Remover**

(Contd. of page 11)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Andy French (AFrench@semproducts.com)
- **Date of preparation / last revision** 06/08/2020 / 13
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flam. Aerosol 1: Aerosols – Category 1  
Press. Gas: Gases under pressure – Compressed gas  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Muta. 1B: Germ cell mutagenicity – Category 1B  
Carc. 1B: Carcinogenicity – Category 1B  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1
- **\* Data compared to the previous version altered.**