

Safety Data Sheet GRIP/AL-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/13/2015 Revision date: 06/13/2017 Version: 3.0

DRIVING SURFACE PERFECTION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : GRIP #4 ADHESION PROMOTER AEROSOL (GRIP/AL-US)

Product group : Aerosol
Other means of identification : UP0799

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

U-POL US Inc 108 Commerce Way Stockertown PA 18083 - USA T 1-800-340-7824 - F 1-800-787-5150

technical.department@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300 (UK +44 (0) 1933 230310 (07:30 - 17:00hrs UK time))

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1 H222 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P261 - Avoid breathing fume, spray, vapors

P263 - Avoid contact during pregnancy/while nursing

P280 - Wear eye protection, protective clothing, protective gloves

P302+P352 - If on skin: Wash with plenty of water P312 - Call a POISON CENTER if you feel unwell

2.3. Other hazards

No additional information available

06/13/2017 EN (English US) SDS ID: GRIP/AL-US Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|--------------|--------------------|---------|--|
| toluene | (CAS No) 108-88-3 | 43 - 63 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Acetone | (CAS No) 67-64-1 | 5 - 23 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| xylene | (CAS No) 1330-20-7 | < 5 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 |
| ethylbenzene | (CAS No) 100-41-4 | < 5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container: may burst if heated.

Reactivity : Extremely flammable aerosol. Pressurized container: may burst if heated.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors,

fume, spray. Avoid contact with skin and eyes.

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Collect spillage.

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, fume, spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contamina

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Storage temperature : < 25 °C

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters GRIP #4 ADHESION PROMOTER AEROSOL (GRIP/AL-US)

| ACGIH | Not applicable | |
|--------------------|-----------------|------------------------------|
| OSHA | Not applicable | |
| toluene (108-88-3) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | Remark (ACGIH) | Visual impair; female repro; |
| OSHA | Remark (OSHA) | (2) See Table Z-2. |

| ethylbenzene (100-41-4) | | | |
|-------------------------|------------------------|-----------------------------------|--|
| ACGIH | ACGIH TWA (ppm) | 20 ppm | |
| ACGIH | Remark (ACGIH) | URT irr; kidney dam (nephropathy) | |
| OSHA | OSHA PEL (TWA) (mg/m³) | 435 mg/m³ | |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm | |

| xylene (1330-20-7) | | |
|--------------------|------------------------|---------------------------|
| ACGIH | ACGIH TWA (ppm) | 100 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| ACGIH | Remark (ACGIH) | URT & eye irr; CNS impair |
| OSHA | OSHA PEL (TWA) (mg/m³) | 435 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Acetone (67-64-1) | | |
|-------------------|------------------------|--------------------------|
| ACGIH | ACGIH TWA (ppm) | 250 ppm |
| ACGIH | ACGIH STEL (ppm) | 500 ppm |
| ACGIH | Remark (ACGIH) | eye irr; CNS impair; BEI |
| OSHA | OSHA PEL (TWA) (mg/m³) | 2400 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Protective clothing. Safety glasses.







Materials for protective clothing : Impermeable clothing. Hand protection : Protective gloves. Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Aerosol. Appearance Color : Cloudy Odor Odourless. : No data available Odor threshold : No data available рΗ Relative evaporation rate (butyl acetate=1) No data available : Not applicable Melting point Freezing point : No data available **Boiling point** : No data available : No data available Flash point Auto-ignition temperature No data available Decomposition temperature : No data available Flammability (solid, gas) No data available : No data available Vapor pressure Relative vapor density at 20 °C : No data available

Solubility : insoluble in water, soluble in most organic solvents.

: No data available

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

Explosive properties : Pressurized container: may burst if heated.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

Relative density

MIR : 2.5

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| ethylbenzene (100-41-4) | |
|-----------------------------------|--------------------------------------|
| ATE US (gases) | 4500 ppmV/4h |
| ATE US (vapors) | 11 mg/l/4h |
| ATE US (dust, mist) | 1.5 mg/l/4h |
| xylene (1330-20-7) | |
| ATE US (dermal) | 1100 mg/kg body weight |
| ATE US (dust, mist) | 1.5 mg/l/4h |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| toluene (108-88-3) | |
| IARC group | 3 - Not classifiable |
| ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| | |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

3 - Not classifiable

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity - repeated

exposure

: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified Symptoms/effects after skin contact : Irritation.

SECTION 12: Ecological information

12.1. Toxicity

xylene (1330-20-7)
IARC group

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1950 AEROSOLS, 2.1, (D)

Class (ADR) : 2 - Gases
Classification code (ADR) : 5F

Hazard labels (ADR) : 2.1 - Flammable gases



Tunnel restriction code (ADR) : D

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LQ : 1I Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| toluene | CAS No 108-88-3 | 43 - 63% |
|---------------|------------------|----------|
| propan-2-ol | CAS No 67-63-0 | < 5% |
| ethylbenzene | CAS No 100-41-4 | < 5% |
| chlorobenzene | CAS No 108-90-7 | < 5% |
| xylene | CAS No 1330-20-7 | < 5% |

toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 1000 lb

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 1000 lb

xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 100 lb

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporing requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

| toluene (108-88-3) | | | | |
|--|--|---|---|----------------------------------|
| U.S California - Proposition 65 - Carcinogens List | U.S California - Proposition 65 - Developmental Toxicity | U.S California - Proposition 65 - Reproductive Toxicity - Female | U.S California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | Yes | Yes | Yes | 7000 |
| ethylbenzene (100-41-4) | | | | |
| U.S California - Proposition 65 - Carcinogens List | U.S California - Proposition 65 - Developmental Toxicity | U.S California - Proposition 65 - Reproductive Toxicity - Female | U.S California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes | No | No | No | 54 |

SECTION 16: Other information

Revision date : 03/16/2017

Full text of H-phrases:

| At Of 11 prinaded. | |
|--------------------|---|
| H222 | Extremely flammable aerosol |
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H351 | Suspected of causing cancer |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard

: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity

: 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating source or must be heated under confinement before initiation.



SDS US UPOL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.

06/13/2017 EN (English US) SDS ID: GRIP/AL-US 8/8