



TIGERSEAL™

Polyurethane Sealant and Adhesive

Description

TIGERSEAL™ is a one component urethane sealant and adhesive that is ideal for a number of automotive applications. TIGERSEAL™ will permanently seal and bond body panels and trim as well as seal around windows, doors, lights etc. TIGERSEAL™ will bond to most materials, such as steel, aluminum, glass and most plastics. TIGERSEAL™ is not approved to install windscreens. Product does not have UV protection nor does it contain biocide, so it is recommended to over-coat in areas with prolonged exposure to sunlight or moisture.

Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Surface preparation and instructions for use

TIGERSEAL™ PU sealant and adhesive can be used on the following surfaces:-

- Steel, aluminum, brass, iron.
- Fiber Glass and most plastics.
- Glass.
- Wood.
- Ceramics.
- Paint.

Surfaces should be clean, dry and free from grease.

Tool with water only. Tooling with solvent is NOT suggested.

Application

Apply with a standard cartridge caulking gun.

Shelf Life and storage information

9 months from delivery if stored in ideal conditions.

Minimum storage temperature 41°F

Maximum storage temperature 95°F

Storage for prolonged periods above 95°F will result in a reduction of shelf life.

To extend the useful life after opening, cover the nozzle tip with aluminium foil.

Drying time

30-60 mins. to skin.

0.25" per 24 hours to cure through at 72°F and relative humidity of 50%.

Over-painting

TIGERSEAL™ may be over-painted with most paint systems once fully cured. Can be over-painted once it has skinned if using polyurethane paints. The drying of synthetic paint may be retarded. Household gloss will not dry over this product.

Product codes

UP0727 – Black 310ml cartridge.

UP0728 – White 310ml cartridge.

UP0729 – Gray 310ml cartridge.

UP0736 – Beige 310ml cartridge.

UP0771 – White 300ml sausage

UP0770 – Gray 300ml sausage

U-POL US, Inc., 108 Commerce Way, Easton, PA 18040

Tel: (800) 340 7824; Fax: (800) 787 5150

Email: sales-us@u-pol.com Website: www.u-pol.com