SAFETY DATA SHEET

This document is not intended for general distribution.

It can be used as the basis for a general distribution document if appropriate changes are made to the identification section.

Product Code: 150622-1A

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: L-43 Paint Remover Aerosol

MANUFACTURER'S NAME: PBE Jobbers

ADDRESS: 2921 Syene Rd.

Madison, WI 53713

EMERGENCY PHONE (CHEMTREC):800.424.9300

INFORMATION PHONE: 608-274-8797 Product Use: Paint remover

2. HAZARDS IDENTIFICATION

CLASSIFICATION

Flammable aerosol

Gas under pressure Liquefied gas

Skin Corrosion/Irritation 2 Eye Damage/Irritation 2A Carcinogenicity 2



SIGNAL WORD:

Danger

Hazard Statements

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

Precautionary Statements

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat/sparks/open flames/hot surfaces - No smoking

Do not spray on an open flame or other igntion source

Pressurized container - Do not pierce or burn, even after use

Wash hands thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Use personal protective equipment as required

Specific treatment (see ... on this label)

Take off contaminated clothing and wash before reuse

IF ON SKIN: Wash with soap and water

SDS for: 150622-1A Page 1 of 6

Printed: 7/23/2015

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If exposed or concerned: Get medical advice/attention If skin irritation occurs: Get medical advice/attention If eye irritation persists: Get medical advice/attention Store locked up

Protect from sunlight. Store in a well-ventilated place and protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Dispose of contents/container to comply with all local, state, and federal regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Percent
ACETONE	67-64-1	50.00
PROPANE	74-98-6	15.00
METHANOL	67-56-1	14.00
2-BUTOXYETHANOL	111-76-2	9.00
XYLENE, MIXED ISOMERS	1330-20-7	6.60
2-BUTANONE, METHYL ETHYL KETONE	78-93-3	4.00
ETHYLBENZENE	100-41-4	1.40

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes . Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

INGESTION: Not a likely route of exposure.

Most important symptoms/effects, acute and delayed: Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed: None known.

SDS for: 150622-1A Page 2 of 6

5. FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media: Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

Specific hazards arising from the chemical: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes

Special equipment and precautions for fire-fighters: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Methods and materials for containment and cleaning up: Clean up with absorbent material and place in closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

Conditions for safe storage, including any incompatibilities: Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

SDS for: 150622-1A Page 3 of 6

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ACETON E 67-64-1	PEL-TWA: 750 ppm	TLV-TWA 500 ppm TLV-STEL 750 ppm	
PROPANE 74-98-6	Not established	blished TWA: 1000 ppm	
METHANO L 67-56-1	PEL: 200 ppm	TWA: 200 ppm; STEL: 250 ppm	NIOSH: REL: 200 ppm: STEL: 250 ppm;
2-BUTOXYETHANOL 111-76-2	PEL-TWA: 50 ppm; PEL-Ceiling: Not determined	TLV-TWA: 20 ppm; TLV-STEL: Not determined	
XYLENE, MIXED ISOMERS 1330-20-7	PEL: 100 ppm	TLV: 100 PPM STEL: 150 ppm, 15 minutes	
2-BUTANONE, METHYL ETHYL KETONE			
TWA: 100 ppm, 8 hour 100-41-4		TWA: 100 ppm, 8 hour STEL: 125 ppm, 8 hour	

Appropriate engineering controls: Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

Individual protection measures:

Respiratory protection: None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air-line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

Eye protection: None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated

Other protective clothing or equipment: None under normal use. However, use of solvent- resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Aerosol product	Odor: Acetone
Vapor Pressure: Not determined	Odor threshold: Not determined

SDS for: 150622-1A Page 4 of 6

Vapor Density: Heavier than air

Density: Not determined

Freezing point: Not determined

Boiling point: Not determined

Evaporation rate: Slower than ether

Explosive Limits: Not applicable

Autoignition temperature: Not determined

Viscosity: Not determined

pH: Not applicable

Melting point: Not determined

Solubility: Not determined

Flash point: Not determined

Flammability: Level 3 Aerosol

Partition coefficient (n- Not determined

octanol/water): Decomposition

temperature: Not determined

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

Incompatible materials:

Acids, Bases, Strong oxidizing agents

Hazardous decomposition products:

Carbon dioxide, carbon monoxide, smoke, fumes, and other products of incomplete combustion.

11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

14. TRANSPORT INFORMATION

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Cleaning Compound, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

16. OTHER INFORMATION

Date revised: 2015-07-23 Revision 0

Date Printed: 2015-07-23

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE

SDS for: 150622-1A Page 5 of 6

Printed: 7/23/2015

OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

SDS for: 150622-1A Page 6 of 6

Printed: 7/23/2015